

SAFETY DATA SHEET

24/7 EMERGENCY PHONE CONTACT

Product Name: DYNABOND Two-Part Quick Set Frame Adhesive

SDS Version No.: 1.0 Issue Date: January 2022 Revision Date: N/A

1 (800) 535-5053 Infotrac United States and Canada

+1 (352) 323-3500 Infotrac International (Call collect)

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: DYNABOND Two-Part Quick Set Frame Adhesive **PRODUCT DESCRIPTION:** Adhesive PRODUCT USAGE: Adhesive used to bond screen printing mesh to frames

SUPPLIER

NBC Meshtec Americas Inc. 512 Kingsland Drive Batavia, IL 60510 Website: nbcmeshtec.com Phone: 1 (800) 235-5056 Fax: 1 (630) 293-5647

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

Health:

Eye Irritation, Category 2A Target Organ Toxicity (Single exposure), Category 3 **Physical:** Flammable Liquids, Category 2 GHS LABEL



SIGNAL WORD: DANGER HAZARD STATEMENTS

H225: Highly flammable liquid and vapor.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

PRECAUTIONARY STATEMENT(S)

Prevention:

P210: Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking.

- P233: Keep container tightly closed.
- P240: Ground and bond container and receiving equipment.
- P241: Use explosion-proof [electrical/ventilation/lighting/...] equipment.
- P242: Use non-sparking tools.
- P243: Take action to prevent static discharges.
- P280: Wear protective gloves/protective clothing/eye protection/face protection.
- P264: Wash skin thoroughly after handling.
- P261: Avoid breathing dust/fume/gas/mist/vapors/spray.
- P271: Use only outdoors or in a well-ventilated area.

Response:

- P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
- P370+P378: In case of fire: Use water spray, alcohol resistant foam, dry chemical, or carbon dioxide to extinguish.

P305+P351+P338: IF IN EYES: Rinse carefully with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.

P337+P313: If eye irritation persists: Get medical advice/attention.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312: Call a POISON CENTER/doctor/physician if you feel unwell.

Storage:

P235: Keep cool. P403+P233: Store in a well-ventilated place. Keep container tightly closed. P405: Store locked up.

Disposal:

P501: Dispose of contents/container in accordance with applicable federal/state/local regulations.

3. COMPOSITION INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
Acetone	65 - 95	67-64-1

4. FIRST AID MEASURES

EYES: Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

SKIN: Wash off with soap and plenty of water. Consult a physician.

INGESTION: DO NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

INHALATION: If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Use water spray, alcohol-resistant foam, dry chemical, or carbon dioxide. **HAZARDOUS COMBUSTION PRODUCTS:** N/A

EXPLOSION HAZARDS: Extremely flammable liquid and vapor. Vapors/dust may cause flash fire or explosion. Vapors can travel to a source of ignition and flash back. Empty containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. Also, do not reuse containers without commercial cleaning or reconditioning.

FIRE FIGHTING PROCEDURES: As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear. Water may be ineffective. Water spray to cool containers or protect personnel. Use with caution. Water runoff can cause environmental damage. Dike and collect water used to fight fire.

Small fires: Carbon dioxide or dry chemical.

Large fires: Alcohol-type aqueous film-forming foam or water spray.

HAZARDOUS DECOMPOSITION PRODUCTS: N/A

COMMENTS: Use water spray to cool unopened containers.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Wear appropriate personal protective equipment. Eliminate all sources of ignition. Prevent additional discharge of material if able to do so safely. Do not touch or walk through spilled material. Avoid runoff into storm sewers and ditches which lead to waterways. Ventilate spill area. Stay upwind of spill. Use water mist or spray to disperse vapors. Collect spilled material for disposal. Use only non-combustible material for clean-up. Use clean, non-sparking tools to collect absorbed materials. Remove from surface by skimming or with suitable absorbent. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Clean up spill area with decontaminant solution composed of concentrated ammonia (5 percent), detergent (2 percent), and water (93 percent). Cover spill area with suitable absorbent material. Pour decontaminant solution over spill area and allow to react for at least 10 minutes. Collect material in open-head metal container. Flush spill area with water spray after cleanup.

LARGE SPILL: Wear suitable protective equipment. Contain spill. Soak up with absorbent material and transfer to a container for disposal according to local/state/federal regulations.

7. HANDLING AND STORAGE

HANDLING: Use only in a well-ventilated area. Avoid breathing vapor, fumes, or mist. Avoid contact with eyes, skin, and clothing. Ground and bond containers when transferring material. Use spark-proof tools and explosion proof equipment.
STORAGE: Keep away from heat, sparks, and flame. Store containers in a cool, well-ventilated place. Keep container closed when not in use.

SHELF LIFE: 24 months

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)				
	EXPOSURE LIMITS			
Chemical Name	Туре		ppm	mg/m³
	OSHA PEL	TWA	1000 [1]	2400 [1]
Acetone		TWA	500 ^[2]	[2]
	ACGIH TLV	STEL	750 ^[2]	[2]

Footnotes:

1. The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors.

2. Eye & upper respiratory tract irritation, central nervous system impairment, hematologic effects, substances for which there is a Biological Exposure Index or Indices. Not classifiable as a human carcinogen.

ENGINEERING CONTROLS: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Safety glasses. Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US).

- **SKIN:** Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.
- **RESPIRATORY:** Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US).

PROTECTIVE CLOTHING: Apron recommended.

WORK HYGIENIC PRACTICES: Personal hygiene is an important work practice exposure control measure and the following general measures should be taken when handling this material: (1) Do not store, use, and/or consume foods, beverages, tobacco products, or cosmetics in areas where this material is stored. (2) Wash hands and face carefully before eating, drinking, using tobacco, applying cosmetics, or using the restroom. (3) Wash exposed skin promptly to remove accidental splashes of contact with this material.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid ODOR: Acetone COLOR: Clear pH: N/A PERCENT VOLATILE: N/A FLASH POINT AND METHOD: -17°C (1.4°F) TCC FLAMMABLE LIMITS: 2.5% (Acetone) to 12.8% (Acetone) AUTOIGNITION TEMPERATURE: N/A VAPOR PRESSURE: Acetone: 533.3 hPa (400.0 mmHg) at 39.5°C (103.1°F) 245.3 hPa (184.0 mmHg) at 20.0°C (68.0°F) VAPOR DENSITY: N/A BOILING POINT: Acetone: 56°C (133°F) at 1,013 hPa (760 mmHg) - lit. MELTING POINT: Acetone: Melting point/range: -94°C (-137°F) - lit. POUR POINT: N/A THERMAL DECOMPOSITION: N/A SOLUBILITY IN WATER: Partial EVAPORATION RATE: N/A SPECIFIC GRAVITY: 0.842 VISCOSITY: N/A MOLECULAR WEIGHT: N/A (VOC): 0 g/L

10. STABILITY AND REACTIVITY

REACTIVITY: Yes

STABILITY: Stable under recommended storage conditions.

CONDITIONS TO AVOID: Heat, flame, and sparks. Extremes of temperature and direct sunlight.

POSSIBILITY OF HAZARDOUS REACTIONS: Vapors may form explosive mixture with air.

HAZARDOUS DECOMPOSITION PRODUCTS: N/A

INCOMPATIBLE MATERIALS: Bases, oxidizing agents, reducing agents, acetone react violently with phosphorous oxychloride.

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

Chemical Name	ORAL LD₅₀ (rat)	DERMAL LD₅₀ (rabbit)	INHALATION LC50 (rat)
Acetone	5800 mg/kg [Rat]	7426 mg/kg [guinea pig]	50100 mg/m3 [rat] 8h
DERMAL LD50: Not	yet determined for this produc	t	

ORAL LD₅₀: Not yet determined for this product INHALATION LC₅₀: Not yet determined for this product CARCINOGENICITY IARC: Not listed NTP: Not listed OSHA: Not listed

12. ECOLOGICAL INFORMATION

BIOACCUMULATION/ACCUMULATION: Does not bioaccumulate.

AQUATIC TOXICITY (ACUTE)

Notes: CAS # 67-64-1:

Toxicity to fish LC50 - Oncorhynchus mykiss (rainbow trout) - 5,540 mg/l - 96 h

Toxicity to daphnia and other aquatic invertebrates LC50 - Daphnia magna (Water flea) - 8,800 mg/l - 48 h Toxicity to algae Remarks: no data available

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose of in accordance with all current local, state, and federal regulations. **EMPTY CONTAINER:** Dispose of as unused product.

DOT (DEPARTMENT OF TRANSPORTATION) PROPER SHIPPING NAME: Adhesives containing flammable liquid PRIMARY HAZARD CLASS/DIVISION: 3 UN/NA NUMBER: UN1133 PACKING GROUP: II



LABEL:

SPECIAL SHIPPING NOTES: Do not expose to temperature below 7°C/45°F AIR (ICAO/IATA) SHIPPING NAME: Adhesives *containing flammable liquid* UN/NA NUMBER: UN1133 PRIMARY HAZARD CLASS/DIVISION: 3 PACKING GROUP: II



NOTE: Passenger air max: 5L Packages may not exceed 30kg gross weight

15. REGULATORY INFORMATION

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HEALTH HAZARDS: FIRE HAZARD, ACUTE HEALTH HAZARD, CHRONIC HEALTH HAZARD

313 REPORTABLE INGREDIENTS: None

302/304 EMERGENCY PLANNING

EMERGENCY PLAN: None

CERCLA (COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION, AND LIABILITY ACT) CERCLA REGULATORY: CAS # 67-64-1 Acetone, RQ=5000 lbs.

Chemical Name	Wt.%	CERCLA RQ
Acetone	65 - 95	5,000
TSCA (TOXIC SUBSTANCE CONTROL ACT)		

Ch	hemical Name	CAS
Ac	cetone	67-64-1

TSCA REGULATORY: All components of this product are listed on the TSCA Inventory. **REGULATIONS**

STATE REGULATIONS: CAS # 67-64-1 Pennsylvania Right-To-Know Act, New Jersey Right to Know Act, Massachusetts Hazardous Substance, CA Hazardous Substance, Delaware Air Quality Management, Idaho Air Pollutant, Maine Hazardous Air Pollutant, Minnesota Hazardous Substance, New York Hazardous Substance, Washington PELs for Air Contaminants

CALIFORNIA PROPOSITION 65: None

CANADA WHMIS HAZARD SYMBOL AND CLASSIFICATION



WHMIS (WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM): Controlled Product WHMIS CLASS: B, D

DOMESTIC SUBSTANCE LIST (INVENTORY): All components of this product are listed on the Domestic Substances List.


16. OTHER INFORMATION

PREPARED BY: SDS Regulatory Specialist **REVISION SUMMARY:** N/A

Date Revised: 01/27/2022







HMIS RATINGS NOTES: (X) - site specific

MANUFACTURER DISCLAIMER: The information contained in the present sheet is based on our knowledge, on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product. This document must not be regarded as a guarantee on any specific product property. The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.