

PRESS WASH

DYNACHEM Press Wash can be used for cleaning ink off screens during on-press color changes, or before storing screens. Ideal for removing ink from squeegees, floodbars, and other equipment as well. DYNACHEM Press Wash evaporates quickly, leaving no residue.

FEATURES

- Effectively dissolves most inks, including conventional/solvent, UV, plastisol, water based, silver, and carbon.
- Reduces solvent cleaning volumes by as much as 70%, reducing both emissions and waste handling.
- Can be applied manually or in an enclosed automatic screen washing system, providing superior product life and economy.

INSTRUCTIONS

- Scrape any excess ink from screen.
- Apply DYNACHEM Press Wash by squirt bottle, pneumatic sprayer, or rag to the ink side of the screen.
- Thoroughly agitate ink with a rag or scrubber, then wipe up all dissolved ink.
- Reapply if necessary, and follow with a dry rag, wiping on both sides of the screen.
- The screen will be ready for printing or tape application within 20 seconds.

PROPERTIES

APPEARANCE / ODOR

**Clear liquid,
ether-like odor**

SPECIFIC GRAVITY

0.95 @ 68°F (20°C)

pH

Neutral

VOC

950 grams/liter

FLASH POINT

118°F (48°C)

INK TYPES

**Plastisol, UV,
Conventional/Solvent,
Waterbased**

APPLICATION

Textile, Graphic